

INSTALLATION INSTRUCTIONS FLEXIBLE MOULDINGS

ORAC®
DECOR

INSTALLATIE VAN FLEXIBELE LIJSTEN | INSTALLATION DES MOULURES FLEXIBLES |
INSTALLATION VON FLEXIBELE LEISTEN | INSTALACIÓN MOLDURAS FLEXIBLE |
ИНСТРУКЦИЯ ПО УСТАНОВКЕ ГИБКИЕ ПРОФИЛИ

UM303 - 05/2019

SX180F



WWW.ORACDECORUSA.COM

1

Ready?

ATMOSPHERE & SURFACE

Ready? Set? Go!

✓ INSTALLATION
GUARANTEE



Storage and installation conditions: Store profiles and adhesives at room temperature and wait 24 hours before installing.

Opslag- en plaatsingsvoorwaarden: Plaats profielen en lijmen 24 uur vóór de installatie op kamertemperatuur.

Conditions d'installation et de stockage: Stockez les profils et les colles à température ambiante 24 heures avant la pose.

Lager- und Installationsbedingungen: Profile und Kleber 24 Stunden vor Verlegung bei Zimmertemperatur lagern.

Condiciones de almacenamiento y de instalación: Colocar molduras y adhesivos en el lugar 24 horas antes de la aplicación.

Условия хранения и монтажа: Оставьте профили и клей в комнате, которой планируется монтаж, на 24 часа.



Dust free
Stofvrij
Sans poussière
Staubfrei
Libre de polvo
Удалите пыль



Sand and wash surface
Schoor en reinig de ondergrond
Poncez et nettoyez la surface
Schleifen und reinigen Sie den Untergrund
Superficie lisa y limpia
Очистите поверхность



Flat wall & ceilings
Vlakke wand en plafond
Mur et plafond plats
Plane Wand und Decke
Paredes y techos lisos
Выверните стены и потолки



Dry
Droog
Sec
Trocken
Seco
Высушите



No grease
Vetvrij
Sans graisse
Fettfrei
Sin grasa
Обезжирьте

2

Set?

DECOFIX ADHESIVES



Interior, porous and dry surface
Binnen, poreuze en droge ondergronden
Pose à l'intérieur, surfaces poreuses, pièces non humides
Innen, poröse/saugfähig, und trockene Untergründe
Interior, superficies porosas y secas
Для внутренних работ, пористых и сухих поверхностей



Heavy profiles
Zware lijsten
Grandes moulures
Grosse Profilen
Perfiles pesados
Тяжелые профили

or
of
ou
oder
или



Exterior, non-porous or humid surface
Buiten, niet-poreuze of vochtige ondergronden
Pose à l'extérieur, surfaces non poreuses ou environnement humide
Außen, nicht-poröser/saugfähige Untergrund oder Feuchträume
Exterior, superficies no porosas o ambientes húmedos
Для внешних работ, непористых или влажных профилей



Seal wall/ceiling
Verbinding muur/plafond
Collage mur/plafond
Verbindung Wand/Decke
Adherencia techos/paredes
Стены/потолки



DecoFix Pro

Strong, water-based acrylic installation adhesive

FDP-500 310ml | 7 > 8m
FDP-600 4200ml | 65 > 110m



DecoFix Power

Very strong MS-Polymer-based installation adhesive

FDP-700 290 ml | 7 > 8m



Joints between mouldings
Verbinding tussen profielen
Joints entre les profils
Nahtverbindungen zwischen Profilen
Uniones de los perfiles
Стыки между профилями



DecoFix Extra

Polyurethane-based adhesive

FX-200 310ml | min. 80m
FX-210 tube 80ml | min. 20m



3 Go!



INSTALLATION

Also see general instructions for mounting | Zie ook de algemene instructies voor montage | Voir aussi les instructions générales pour montage | Siehe auch allgemeine Instruktionen für Montage | Ver instrucciones generales para montaje | Также смотрите общие инструкции по установке

INSTALLATION INSTRUCTIONS

FLEXIBLE MOULDINGS

ONLY FULL GUARANTEE WITH DECOFIX
 VOLLEDIGE GARANTIE ENKEL BIJ GEBRUIK VAN DECOFIX
 GARANTIE TOTALE UNIQUEMENT AVEC COLLE DECOFIX
 VOLLSTÄNDIGE GARANTIE NUR BEI DER VERWENDUNG VON DECOFIX
 GARANTÍA COMPLETA SÓLO SI SE UTILIZA DECOFIX
 ГАРАНТИЯ НА ПРОДУКЦИЮ ДЕЙСТВУЕТ ТОЛЬКО ПРИ ИСПОЛЬЗОВАНИИ КЛЕЯ DECOFIX



PRODUCT OVERVIEW FLEXIBLE MOULDINGS

Part # Profile	Min. Inside Radius	Min. Outside Radius	Min. Arch Radius
CX100F	6'7"	6'7"	N/A
CX106F	11'10"	11'10"	N/A
CX109F	5'3"	5'3"	N/A
CX110F	5'11"	5'11"	N/A
CX123F	9'3"	9'3"	N/A
CX124F	5'3"	5'3"	N/A
CX127F	7'11"	7'11"	N/A
CX132F	2'4"	2'4"	N/A
CX148F	5'11"	5'11"	N/A
CX188F	3'8"	3'8"	N/A
CX189F	3'	3'	N/A
CX190F	1'	1'	4'
DX162F	8"	8"	2'6"
DX163F	1'2"	1'2"	N/A
DX174F	1'	1'	9'2"
DX182F	1'2"	1'2"	N/A
DX183F	1'4"	1'4"	N/A
DX184F	1'6"	1'6"	N/A
FC200	5'3"	5'3"	N/A
FC201	6'7"	6'7"	N/A
FC211	8'3"	8'3"	N/A
FC212	4'	4'	N/A
FC213	9'3"	9'3"	N/A

Part # Profile	Min. Inside Radius	Min. Outside Radius	Min. Arch Radius
FC214	4'8"	4'8"	N/A
FC215	5'3"	5'3"	N/A
FC216	11'2"	11'2"	N/A
FC217	12'6"	12'6"	N/A
FC218	11'10"	11'10"	N/A
FC220	13'2"	13'2"	N/A
FC230	5'	5'	N/A
FC240	8'11"	8'11"	N/A
FC250	2'4"	2'4"	N/A
FC260	4'4"	4'4"	N/A
FC301	10'6"	10'6"	N/A
FC302	8'3"	8'3"	N/A
FC303	5'11"	5'11"	N/A
FC304	8'3"	8'3"	N/A
FC308	4'	4'	N/A
FC321	4'8"	4'8"	N/A
FC322	5'3"	5'3"	N/A
FC331	13'10"	13'10"	N/A
FC333	9'11"	9'11"	N/A
FC334	12'6"	12'6"	N/A
FC339	12'6"	12'6"	N/A
FC341	13'2"	13'2"	N/A
FC373	3'4"	3'4"	N/A

Part # Profile	Min. Inside Radius	Min. Outside Radius	Min. Arch Radius
FC374	4'4"	4'4"	N/A
FC402	9'11"	9'11"	N/A
FC602	3'4"	3'4"	N/A
FC901	19'9"	19'9"	N/A
FC902	19'9"	19'9"	N/A
FP1020	1'	1'	2'6"
FP2020	1'	1'	2'6"
FP3020	1'8"	1'8"	5'6"
FP4020	1'4"	1'4"	6'1"
FP5020	1'	1'	N/A
FP5021	8"	8"	2'2"
FP6020	1'	1'	7'7"
FP7010	8"	8"	N/A
FP7020	1'	1'	N/A
FP7030	1'	1'	7'7"
FP7040	1'4"	1'4"	9'9"
FP7070	1'	1'	7'
FP8020	1'4"	1'4"	4'
FP8030	8"	8"	2'2"
FP8040	1'	1'	6'1"
FP8050	2'8"	2'8"	6'7"
FP8060	2'8"	2'8"	6'1"
FP9010	1'4"	1'4"	9'5"

Part # Profile	Min. Inside Radius	Min. Outside Radius	Min. Arch Radius
FP9020	1'	1'	N/A
FP9040	1'	1'	2'6"
FP9050	8"	8"	1'11"
FP9900	8"	8"	7'7"
FP9901	8"	8"	5'6"
PX103F	8"	8"	2'6"
PX120F	1'	1'	3'4"
PX144F	8"	8"	6'8"
PX175F	1'	1'	2'6"
SX104F	1'4"	1'4"	N/A
SX105F	1'	1'	N/A
SX118F	1'4"	1'4"	N/A
SX137F	1'4"	1'4"	N/A
SX138F	1'4"	1'4"	N/A
SX155F	1'	1'	N/A
SX157F	1'2"	1'2"	7'11"
SX165F	1'4"	1'4"	N/A
SX172F	1'2"	1'2"	N/A
SX173F	1'6"	1'6"	N/A
SX179F	1'2"	1'2"	N/A
SX180F	1'6"	1'6"	N/A
SX187F	1'4"	1'4"	N/A